

Jacobi



- Medium activity
- Proven drinking water adsorbent
- High density
- High wettability
- High hardness and abrasion resistance
- Proven superior for multiple reactivations
- Excellent adsorption capacity
- Both adsorption and transport pores
- Typical Applications Treatment of municipal drinking water
- Production of soft drinks and beer
- Dechlorination of process water
- Available Particle Sizes 20x50 mesh (0.30 - 0.85 mm)
- 12x40 mesh (0.425 - 1.70 mm)
- 8x30 mesh (0.60 - 2.36 mm)
- 8x20 mesh (0.85 - 2.36 mm)
- 8x16 mesh (1.18 - 2.36 mm)
- ovals ANSI / NSF standard 61
- AWWA B604-96
- EN12915
- The polyethylene valve bag from Jacobi sets the standard in the industry for clean, durable and safe handling.

TECHNICAL DATASHEET



Standard Packaging 25 kg bag (55 lb) • 500 kg bulk bag (1100 lb)

AquaSorb® 1000

granular coal based

activated carbon

AquaSorb® 1000 is a highly economical, medium activity granular activated carbon manufactured by steam activation from select grades of bituminous coal. The perfect balance between adsorption and transport pores provides optimum performance in a wide range of water treatment applications. The product is a high density adsorbent and provides maximum volume activity. The high hardness and mechanical strength ensures negligible losses during backwashing, air scouring and multiple reactivations.

Specification

Iodine number	min. 850 mg/g
Moisture content	max. 5%
Total ash content	max. 15%
Wettability	min. 95%
Hardness min	. 95%

Typical Properties

Surface area	900 m ² /g
Methylene blue number	200 mg/g
Total pore volume	0.88 cm ³ /g
Water soluble ash	0.2%
Apparent density	510 kg/m ³
pH	8-11

CAUTION Activated carbon is a strong oxidizing agent and can remove oxygen from air under wet or humid conditions. Care should be taken when entering confined spaces where wet activated carbon is present. Ensure the use of correct breathing apparatus. Material Safety Data Sheets should be consulted for further details on procedures in the event of contact with activated carbon. NOTICE Due to the progressive nature of Jacobi Carbons Group and the continually improving design and performance of our products, we reserve the right to change product specifications without prior notification. The information contained in this datasheet is intended to assist a customer in the evaluation and selection of products supplied by Jacobi Carbons. The customer is responsible for determining whether products and the information contained in this document are appropriate for customer's use. Jacobi Carbons assumes no obligation or liability for the usage of the information in this datasheet, no guarantees or warranties, expressed or implied, are provided. Jacobi Carbons disclaims responsibility and the user must accept full responsibility for performance of systems based on this data.